

MASONRE

MASONRE Efflorescence Remover

The MASONRE Efflorescence Remover is a liquid cleaner intended to remove efflorescence, mortar smears, Grout haze, hard water deposits atmospheric staining, and others blemishes on the surface of masonry.

Features and Benefits

- Biodegradable
- Short dwell time
- Brush, roll or spray apply
- User friendly
- Rinses off with water
- Safe on glass

Application Procedures Test Area

Always prepare a test area prior to full application. This will indicate the time required for project completion and suitability of product for effective cleaning of the substrate. Additionally, specific jobsite consumption rates can be calculated after the test area is completed.

Equipment and Tools

This product is designed to be applied by spray, brush or roller. Other equipment required: masking tape, nylon brush, plastic (polyethylene) sheet, should be used for protecting surfaces not to be treated with MASONRE Efflorescence Remover.

Preparation

MASKING: Cover / protect areas where cleaning is not desired, including adjoining surfaces where over spray may travel. Plastic (polyethylene) sheets make a very effective barrier. Test to see affects on any glass or metals that may come in contact with MASONRE Efflorescence Remover.

DO NOT DILUTE.

Application

Apply a thick, even layer of MASONRE Efflorescence Remover onto a **DRY** substrate. Let sit for several minutes then scrub the surface with a nylon brush. Rinse off the substrate and reapply as needed.

Removal and Cleanup

After allowing the product to dwell, rinse the surface with copious amounts water (pressure washer). Do not allow run off to dry on other surfaces.

Safety Requirements

Proper safety procedures should be followed at all times while handling this product. Refer to the Material Safety Data Sheet for important health/safety information before use. MASONRE Efflorescence Remover should only be used for approved applications.

Limitations

Surface temperatures should be 40° to 95°F (5° to 32°C). The product performs effectively at lower temperatures (even at 40°F, 5°C), but the dwell time increases.

Packaging and Coverage

Packaging: Approximately 5 gallons

The product is engineered for thick film build up on vertical and overhead surfaces. Minimum wet film thickness should be **0.5 mils (500 microns)**. **Always test the substrate to ensure accurate coverage rates.** Typical coverage rates are between 150 and 200 ft sq. ft. per gallon.

Technical Data

Appearance	White foam gel
Specific Gravity	1
Boiling Point	Not specified
pH	2
VOC content	N/A

DO NOT ALLOW PRODUCT TO FREEZE!

Notice: The information contained herein is based on our own research and the research of others, and it is provided solely as a service to help users. It is believed to be accurate to the best of our knowledge. However, no guarantee of its accuracy can be made, and it is not intended to serve as the basis for determining this product's suitability in any particular situation. For this reason, purchasers are responsible to make their own tests and assume all risks associated with using this product.

MASONRE Efflorescence Remover

Page 2

02/2012