

# MASONRE

## MASONRE G Heavy Duty Cleaner

The MASONRE G is a safe gel based cleaner intended for the removal of severe black carbon staining, dirt, and grime on sandstone, unpolished granite, brick, concrete and brownstone. **When using on limestone, marble or any calcareous stone limit dwell times to 10-15 minutes.** The product is designed for exterior use on buildings and monuments.

### Features and Benefits

- Biodegradable
- Short dwell time
- Gel clings to vertical surfaces and aids in clean up
- Brush, roll or spray apply
- User friendly

## Application Procedures Test Area

Always prepare a test area prior to full application. This will indicate the time required for project completion and suitability of product for effective cleaning of the substrate. Additionally, specific jobsite consumption rates can be calculated after the test area is completed.

### Equipment and Tools

This product is designed to be applied by brush or roller. Other equipment required: masking tape, plastic (polyethylene) sheet, should be used for protecting surfaces not to be treated with MASONRE G.

### Preparation

**MASKING:** Cover / protect areas where cleaning is not desired, including adjoining surfaces where over spray may travel. Plastic (polyethylene) sheets make a very effective barrier. **The MASONRE G will harm most aluminum and glass surfaces. Protection is required!** Plants should be covered before and during the application.

MASONRE G can be diluted with fresh water before application. Although this product is intended to be used full strength, it may be necessary to dilute the MASONRE G to avoid damage to some masonry surfaces. **ALWAYS TEST** this product to determine acceptable site specific concentrations.

**MIXING:** Thoroughly mix the MASONRE G with a drill. **DO NOT SHAKE.**

### Application

Apply a thick, even layer of MASONRE G onto a wet/damp substrate.

### Dwell Time

The time required for the MASONRE G to adequately clean a substrate is approximately 5-45 minutes. If product begins to dry a second layer of product may be applied directly over the existing one. Apply test panels to determine the dwell time prior to full application of product. **DO NOT ALLOW TO DRY ON SUBSTRATE.**

### Removal and Cleanup

After allowing the product to dwell, rinse the surface with copious amounts water (pressure washer).

### Safety Requirements

Proper safety procedures should be followed at all times while handling this product. Refer to the Material Safety Data Sheet for important health/safety information before use. mason RE G is an acidic gel. It is essential to wear protective clothing and glasses while using this product.

### Limitations

Surface temperatures should be 40° to 95°F (5° to 32°C). The product performs effectively at lower temperatures (even at 40°F, 5°C), but the dwell time increases.

### Packaging and Coverage

Packaging: Approximately 5 gallons

The product is engineered for thick film build up on vertical and overhead surfaces. Minimum wet film thickness should be **0.5 mils (500 microns).** **Always test the substrate to ensure accurate coverage rates.** Typical coverage rates on a rough porous surface are between 80 and 120 sq. ft. per gallon. Coverage rates on a smooth nonporous surface are typically between 350 and 400 sq. ft. per gallon.

### Technical Data

Appearance	Thick clear gel
Specific Gravity	1
Boiling Point	Not specified
pH	3-4
VOC content	<b>NO</b>

**DO NOT ALLOW PRODUCT TO FREEZE!**

**Notice:** The information contained herein is based on our own research and the research of others, and it is provided solely as a service to help users. It is believed to be accurate to the best of our knowledge. However, no guarantee of its accuracy can be made, and it is not intended to serve as the basis for determining this product's suitability in any particular situation. For this reason, purchasers are responsible to make their own tests and assume all risks associated with using this product.

02/2012