

CSP Potassium Silicate Coating

Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : CSP Potassium Silicate Coating

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Paint

1.3. Details of the supplier of the safety data sheet

Cathedral Stone Products
7266 Park Circle Drive
Hanover, MD 21076
T 410-782-9150

1.4. Emergency telephone number

Emergency number : 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Acute Tox. 4 (Oral) H302
Skin Corr. 1A H314
Eye Dam. 1 H318

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS05



GHS07

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage

Precautionary statements (GHS-US) :

P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P264 - Wash thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P312 - If swallowed: Call a poison center/doctor if you feel unwell
P301 + P330 + P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P303 + P361 + P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304 + P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a poison center/doctor
P330 - Rinse mouth
P363 - Wash contaminated clothing before reuse
P405 - Store locked up
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

CSP Potassium Silicate Coating

Safety Data Sheet

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Potassium silicate	(CAS No) 1312-76-1	30 - 35	Acute Tox. 4 (Oral), H302
Water	(CAS No) 7732-18-5	20 - 25	Not classified
Wollastonite (Ca(SiO ₃))	(CAS No) 13983-17-0	5 - 10	Not classified
Limestone	(CAS No) 1317-65-3	1 - 5	Not classified
Mineral spirits	(CAS No) 64475-85-0	1 - 5	Not classified
2-Butoxyethanol	(CAS No) 111-76-2	<1	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Obtain medical attention if breathing difficulty persists.
- First-aid measures after skin contact : Rinse with soap and water. Seek medical attention if irritation develops or persists.
- First-aid measures after eye contact : Remove contact lenses immediately. Flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
- First-aid measures after ingestion : Do not induce vomiting. Give water to victim to drink. Seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory irritation.
- Symptoms/injuries after skin contact : Causes severe skin burns.
- Symptoms/injuries after eye contact : Causes eye damage.
- Symptoms/injuries after ingestion : Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media for surrounding fire.
- Unsuitable extinguishing media : None.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not flammable.
- Explosion hazard : None known.

5.3. Advice for firefighters

- Protection during firefighting : Firefighters should wear full protective gear.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Stop the flow of material, if this is without risk.
- Methods for cleaning up : Confine spill and soak up with absorbent. Place in an approved container and dispose in accordance with local, state and federal regulations.

CSP Potassium Silicate Coating

Safety Data Sheet

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a cool, dry place with adequate ventilation.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Water (7732-18-5)		
ACGIH	Not applicable	
OSHA	Not applicable	
Mineral spirits (64475-85-0)		
ACGIH	Not applicable	
OSHA	Not applicable	
Limestone (1317-65-3)		
ACGIH	Not applicable	
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)
2-Butoxyethanol (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	240 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
Wollastonite (Ca(SiO3)) (13983-17-0)		
ACGIH	Not applicable	
OSHA	Not applicable	
Potassium silicate (1312-76-1)		
ACGIH	Not applicable	
OSHA	Not applicable	

8.2. Exposure controls

Hand protection : Wear impervious gloves to minimize skin contact.
Eye protection : Chemical safety goggles.
Skin and body protection : Wear suitable working clothes.
Respiratory protection : If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Viscous.
Color : Colored
Odor : Slight
Odor threshold : No data available
pH : 11.3

CSP Potassium Silicate Coating

Safety Data Sheet

Melting point	: No data available
Freezing point	: No data available
Boiling point	: 99.2 °C
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Specific gravity	: 1.31
Relative vapor density at 20 °C	: No data available
Solubility	: Complete
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

None

10.5. Incompatible materials

Acids, reactive materials, and ammonium salts.

10.6. Hazardous decomposition products

Not determined.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

MasonRE Mineral Paint	
ATE US (oral)	500.000 mg/kg body weight
Water (7732-18-5)	
LD50 oral rat	> 90 ml/kg
Mineral spirits (64475-85-0)	
LD50 oral rat	> 34600 mg/kg
LC50 inhalation rat (mg/l)	> 21400 mg/m ³ (Exposure time: 4 h)
2-Butoxyethanol (111-76-2)	
LD50 oral rat	470 mg/kg
LD50 dermal rabbit	99 mg/kg

CSP Potassium Silicate Coating

Safety Data Sheet

2-Butoxyethanol (111-76-2)	
LC50 inhalation rat (ppm)	450 ppm/4h
ATE US (oral)	470.000 mg/kg body weight
ATE US (dermal)	220.000 mg/kg body weight

Potassium silicate (1312-76-1)	
LD50 oral rat	1300 mg/kg
ATE US (oral)	1300.000 mg/kg body weight

Skin corrosion/irritation	: Causes severe skin burns and eye damage. pH: 11.5
Serious eye damage/irritation	: Causes serious eye damage. pH: 11.5
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

2-Butoxyethanol (111-76-2)	
IARC group	3 - Not classifiable

Wollastonite (Ca(SiO ₃)) (13983-17-0)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified

Specific target organ toxicity (repeated exposure)	: Not classified
--	------------------

Aspiration hazard	: Not classified
-------------------	------------------

SECTION 12: Ecological information

12.1. Toxicity

2-Butoxyethanol (111-76-2)	
LC50 fish 1	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)

Potassium silicate (1312-76-1)	
LC50 fish 1	301 - 478 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
LC50 fish 2	3185 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

2-Butoxyethanol (111-76-2)	
Log Pow	0.81 (at 25 °C)

Potassium silicate (1312-76-1)	
BCF fish 1	(no bioaccumulation expected)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming	: No known ecological damage caused by this product.
------------------------------	--

CSP Potassium Silicate Coating

Safety Data Sheet

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not a dangerous good as defined in transport regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Water (7732-18-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Limestone (1317-65-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2-Butoxyethanol (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Potassium silicate (1312-76-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State regulations

Limestone (1317-65-3)

U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

2-Butoxyethanol (111-76-2)

U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases::

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 4	Flammable liquids Category 4
Skin Corr. 1A	Skin corrosion/irritation Category 1A
H227	Combustible liquid
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product