

R-97 Water Repellent

R-97 can be applied to brick, grout, unpolished marble, limestone, tile, and other masonry surfaces. The water-based composition is odorless and leaves a natural finish (no sheen). R-97 creates an easily cleanable surface for dirt, oil, grime, tar, soil, etc. on the surface. It works by penetrating into the substrate. It is not topical. After being absorbed, R-97 establishes a powerful chemical network within the substrate pores, keeping moisture and oil out. In addition to keeping treated surfaces dry and making it easy to clean, R-97 does not block the pores, permitting essential vapor transmission.

Features and Benefits

- Safe on glass
- Non-Flammable
- Independent lab tested
- UV stable
- Alkali resistant
- No VOCs, environmentally friendly

Application Procedures

Always prepare a test area prior to full application.

Surface Preparation

Surfaces should be clean, dry and absorbent before sealing with R-97. All surfaces should be pressure washed (low Pressure >600 psi) to ensure R-97 achieves maximum penetration.

Directions

- Apply with sprayer (35 psi or less), brush or roll. DO NOT ATOMIZE
- Saturate surface until it starts to run. A single coat is recommended.
- Allow to dry. Surface will be dry in about an hour.

Note: R-97 works by absorbing into surfaces and reaches its maximum water and oil repellency in 24 hours.

Safety Requirements

Proper safety procedures should be followed at all times while handling this product. Refer to the Safety Data Sheet for important health/safety information before use.

Limitations

- R-97 is not meant to seal cracks
- Not for polished granite or polished marble
- Minimum temperature for application 45° F
- Maximum substrate temperature 90° F
- R-97 can be used on vertical or horizontal substrates (warranties are not available for horizontal surfaces)

Packaging and Coverage

1 gallon, 5-gallon pails and 55-gallon drums. Coverage will vary depending on the porosity of the surface. 200 to 300 sq. ft. per gallon can be expected.

Storage And Shelf Life

This product must be stored at temperatures above freezing and below 78°F -- and at low humidity. DO NOT ALLOW PRODUCT TO FREEZE. Do not store in direct sunlight. The shelf life of an unopened container is 1 year.

After use, fully seal any unused portion in its original container prior to storage. If the product was previously opened or was stored longer than a year, test in an inconspicuous location for effectiveness.

Technical Data

Appearance/Odor	Cloudy liquid, odorless
Specific Gravity	1
Classification	Fluorocarbon Emulsion
Physical Form	Translucent Emulsion
pH (direct reading)	5.4
Non-volatile (1hr @ 105°C, %)	N/A

DO NOT ALLOW R-97 TO FREEZE!

Warning

Not for internal consumption. Keep out of reach of children and animals. Consult Material Safety Data Sheet (MSDS) for specific information.

Notice: The information contained herein is based on our own research and the research of others, and it is provided solely as a service to help users. It is believed to be accurate to the best of our knowledge. However, no guarantee of its accuracy can be made, and it is not intended to serve as the basis for determining this product's suitability in any particular situation. For this reason, purchasers are responsible to make their own tests and assume all risks associated with using this product.