

CSP Graffiti Remover

Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : CSP Graffiti Remover

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Manufacturing

1.3. Details of the supplier of the safety data sheet

Cathedral Stone Products
7266 Park Circle Drive
Hanover, MD 21076
T 410-782-9150

1.4. Emergency telephone number

Emergency number : 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 4 H227
Skin Irrit. 2 H315
Eye Irrit. 2A H319
STOT SE 3 H335

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H227 - Combustible liquid
H302 - Harmful if swallowed
H312 - Harmful if contact if in contact with skin
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H401 - Toxic to aquatic life

Precautionary statements (GHS-US) :

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P264 - Wash thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P302 + P352 - If on skin: Wash with plenty of water
P304 + P312 + P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a poison center/doctor if you feel unwell
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse
P370+P378 - In case of fire: Use media appropriate for surrounding fire to extinguish
P403+P233+P235 - Store in a well-ventilated place. Keep container cool and tightly closed
P405 - Store locked up
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

CSP Graffiti Remover

Safety Data Sheet

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%*	Classification (GHS-US)
Diethylene glycol monobutyl ether	(CAS No) 112-34-5	< 40	Flam. Liq. 4, H227 Eye Irrit. 2A, H319
Benzyl alcohol	(CAS No) 100-51-6	< 20	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Irrit. 2A, H319 Acute Tox. 4 (Inhalation), H332 Acute Aqu. Tox., H401
Dipropylene glycol monomethyl ether	(CAS No) 34590-94-8	< 20	Flam. Liq. 4, H227 Resp. Irrit. 3, H335
Dimethyl sulfoxide	(CAS No) 67-68-5	< 15	Flam. Liq. 4, H227

* Approximate amounts. Exact amounts are a trade secret.

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Do not leave the victim unattended. Remove person to fresh air and keep comfortable for breathing. Obtain medical attention if breathing difficulty persists.
First-aid measures after skin contact	: Rinse with plenty of water while removing contaminated clothing. Continue for at least 15 minutes. If irritation is evident or discoloration persists, seek medical attention.
First-aid measures after eye contact	: Remove contact lenses immediately. Flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops or persists.
First-aid measures after ingestion	: Do not induce vomiting. Give water to victim to drink. Seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Exposure to vapor or mists may cause moderate to severe irritation of respiratory tract. Symptoms may include headache, nausea, coughing, chest pain and vomiting.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness and a burning sensation. Prolonged contact may result in the absorption of potentially harmful amounts of material, with identical symptoms as ingestion.
Symptoms/injuries after eye contact	: Causes eye irritation. Symptoms may include a stinging sensation, excess blinking and tear production, redness and swelling of the conjunctiva.
Symptoms/injuries after ingestion	: Ingestion may cause moderate to severe irritation of the gastrointestinal tract. Symptoms may include nausea, dizziness, and abdominal pain.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Product is flammable at high temperatures. Use extinguishing media for surrounding fire – water fog or fine spray, dry chemical fire extinguishers, carbon dioxide fire extinguishers, alcohol resistant foams are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.
Unsuitable extinguishing media	: High volume water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustible liquid. (Emits toxic fumes such as Carbon monoxide, carbon oxides)
Explosion hazard	: None known.

5.3. Advice for firefighters

Protection during firefighting	: Firefighters should use self-contained, approved breathing apparatus and wear full protective gear. Keep people away. For large volumes, do not allow run-off from fire fighting to enter drains or water courses. Use water spray to cool fully closed containers.
--------------------------------	---

CSP Graffiti Remover

Safety Data Sheet

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Isolate area. Keep unnecessary and unprotected personnel from entering the area. Use appropriate safety equipment.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent undiluted product from entering into soil, ditches, sewers, waterways and/or groundwater.

6.3. Methods and material for containment and cleaning up

For containment : Stop the flow of material, if this is without risk.

Methods for cleaning up : Confine spill and soak up with noncombustible absorbent (such as sand or vermiculite) Place in an approved container and dispose in accordance with local, state and federal regulations.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Prior to each use, mix well. Avoid contamination of any kind. Potential immersion elements such as drum pumps and hoses should be removed after each use. Empty containers should be thoroughly rinsed with water and disposed of according to local regulations. Do not completely fill containers with paint waste. Until mostly dry wet paint waste can have the tendency to slightly expand, therefore do not seal containers airtight to allow a breathing period. Care should be exercised when moving in or around product application areas (particularly oversprayed areas) as contacted surfaces become very slippery.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store product in product's manufacturer provided container in a cool, well-ventilated area away from heat, open flames or any ignition sources. Storage temperature should be 4-30 C (38-86 F) at ambient pressure.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Diethylene glycol monobutyl ether (112-34-5)		
ACGIH	ACGIH TWA (ppm)	10 ppm (inhalable fraction and vapor)
OSHA	Not applicable	
Benzyl alcohol (100-51-6)		
ACGIH	Not applicable	
OSHA	Not applicable	
Dimethyl sulfoxide (67-68-5)		
ACGIH	Not applicable	
OSHA	Not applicable	
Dipropylene glycol monomethyl ether (34590-94-8)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	600 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

8.2. Exposure controls

Hand protection : Wear impervious gloves to minimize skin contact.
Eye protection : Safety glasses.
Skin and body protection : Wear suitable working clothes.

CSP Graffiti Remover

Safety Data Sheet

Respiratory protection : If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Odor	: Mild
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 82 °C (179.6 °F)
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: 15 mm Hg @ 20 C
Relative density	: 8.29 lb/gal
Specific gravity	: 0.994
Relative vapor density at 20 °C	: No data available
Solubility	: <10% in water
VOC content	: 286.8 g/l (2.39 lb/gal)
% Volatiles	: >50%
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Hot or cold storage.

10.5. Incompatible materials

Strong oxidizers, acids and alkalis.

10.6. Hazardous decomposition products

Oxides of carbon and other toxic volatiles.

CSP Graffiti Remover

Safety Data Sheet

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Diethylene glycol monobutyl ether (112-34-5)	
LD50 oral rat	5660 mg/kg
LD50 dermal rabbit	2700 mg/kg
ATE US (oral)	3384.000 mg/kg
ATE US (dermal)	2700.000 mg/kg

Benzyl alcohol (100-51-6)	
LD50 oral rat	1230 mg/kg
LD50 dermal rabbit	2 g/kg
LC50 inhalation rat (mg/l)	8.8 mg/l/4h
ATE US (oral)	1230.000 mg/kg
ATE US (dermal)	2000.000 mg/kg

Dimethyl sulfoxide (67-68-5)	
LD50 oral rat	14500 mg/kg
ATE US (oral)	14500.000 mg/kg body weight

Dipropylene glycol monomethyl ether (34590-94-8)	
LD50 oral rat	5400 µl/kg
LD50 dermal rabbit	9500 mg/kg
ATE US (oral)	5230.000 mg/kg body weight
ATE US (dermal)	9500.000 mg/kg body weight

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Diethylene glycol monobutyl ether (112-34-5)	
LC50 fish 1	1300 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Benzyl alcohol (100-51-6)	
LC50 fish 1	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

Dimethyl sulfoxide (67-68-5)	
LC50 fish 1	34000 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
LC50 fish 2	33 - 37 g/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

Dipropylene glycol monomethyl ether (34590-94-8)	
LC50 fish 1	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)

CSP Graffiti Remover

Safety Data Sheet

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Diethylene glycol monobutyl ether (112-34-5)	
BCF fish 1	(no bioconcentration expected)
Benzyl alcohol (100-51-6)	
Log Pow	1.1
Dimethyl sulfoxide (67-68-5)	
Log Pow	-2.03
Dipropylene glycol monomethyl ether (34590-94-8)	
Log Pow	-0.064 (at 20 °C)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not a dangerous good as defined in transport regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Diethylene glycol monobutyl ether (112-34-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.
Benzyl alcohol (100-51-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Dimethyl sulfoxide (67-68-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Dipropylene glycol monomethyl ether (34590-94-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

15.2. US State regulations

Benzyl alcohol (100-51-6)	
U.S. - Massachusetts - Right To Know List U.S. - Minnesota - Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	
Dimethyl sulfoxide (67-68-5)	
U.S. - New Jersey - Right to Know Hazardous Substance List	

CSP Graffiti Remover

Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)

U.S. - Massachusetts - Right To Know List
U.S. - Minnesota - Hazardous Substance List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases::

H227	Combustible liquid - Category 4
H302	Harmful if swallowed - Category 4
H312	Harmful in contact with skin - Category 4
H315	Causes skin irritation Category 2
H319 2A	Causes serious eye irritation Category 2A
H332	Harmful if inhaled
H335	Specific target organ toxicity (single exposure) respiratory Category 3
H401	Toxic to aquatic life

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product