

# CSP Light Duty Paint Remover

## Safety Data Sheet

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : CSP Light Duty Paint Remover

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Paint Stripper

#### 1.3. Details of the supplier of the safety data sheet

Cathedral Stone Products  
7266 Park Circle Drive  
Hanover, MD 21076  
T 410-782-9150

#### 1.4. Emergency telephone number

Emergency number : 1-800-424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Acute Tox. 4 (Oral) H302  
Acute Tox. 4 (Inhalation) H332  
Skin Irrit. 2 H315  
Eye Irrit. 2B H320

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

GHS03

GHS05

Signal word (GHS-US) : Warning, Danger

Hazard statements (GHS-US) : H272 - May intensify fire; oxidizer  
H302+H332 - Harmful if swallowed or if inhaled  
H312 - Harmful in contact with skin  
H315 - Causes skin irritation  
H318 - Causes serious eye damage  
H320 - Causes eye irritation

Precautionary statements (GHS-US) : P210 - Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking.  
P220 - Keep away from clothing and other combustible materials.  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray  
P264 + P265 - Wash hands thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P301 + P316 - If swallowed: Call a poison center/doctor if you feel unwell  
P302 + P352 - If on skin: Wash with plenty of water  
P304 + P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305 + P351 + P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312 - Call a poison center/doctor if you feel unwell  
P317 - Get emergency medical help.  
P321 - Specific treatment (see label).  
P330 - Rinse mouth  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P337 + P313 - If eye irritation persists: Get medical advice/attention  
P354 - Immediately rinse with water for several minutes.

# CSP Light Duty Paint Remover

## Safety Data Sheet

P362 + P364 - Take off contaminated clothing and wash before reuse

P370 + P378 - In case of fire: Use ... to extinguish.

P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS-US)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Phenylmethanol	(CAS No) 100-51-6	30 - 40	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Serious Eye Damage, 1, H318
Hydrogen Peroxide	(CAS No) 7722-84-1	5 to 10	Oxidizing Liq. 3, H272 Acute Tox. 4 (Oral), H302 Serious Eye Damage, 1, H318
N-Phenylacetamide	(CAS No.) 103-84-4	<1	Acute Tox. 4 (Oral), H302

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Obtain medical attention if breathing difficulty persists.
- First-aid measures after skin contact : Rinse with plenty of water. Get medical attention for burns.
- First-aid measures after eye contact : Remove contact lenses immediately. Flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
- First-aid measures after ingestion : Do not induce vomiting. Give water to victim to drink. Seek medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Harmful if inhaled. May cause respiratory irritation.
- Symptoms/injuries after skin contact : Causes skin irritation. Skin contact produces stinging and a white wound that clears in a short period of time. Prolonged contact may cause more serious burns.
- Symptoms/injuries after eye contact : Causes eye irritation. Eye contact produces stinging and a white wound that clears in a short period of time. Prolonged contact may cause more serious burns.
- Symptoms/injuries after ingestion : Harmful if swallowed. May cause gastrointestinal complications.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Use carbon dioxide, foam, dry chemical or water spray.
- Unsuitable extinguishing media : None.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not flammable.
- Explosion hazard : Vapors can travel to a source of ignition and flash back. Closed containers may explode when overheated. Toxic gases may form when product comes in contact with extreme heat.

### 5.3. Advice for firefighters

- Protection during firefighting : Firefighters should wear full protective gear.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Use personal protective equipment as required. Ensure adequate ventilation.

# CSP Light Duty Paint Remover

## Safety Data Sheet

### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Stop the flow of material, if this is without risk.  
Methods for cleaning up : Confine spill and soak up with absorbent. Place in an approved container and dispose in accordance with local, state and federal regulations.

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Wear personal protective equipment/face protection. Avoid contact with eyes and skin. Wash thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect container against physical damage and store in a cool, dry ventilated area. Do not store above 120F (48C).

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Benzyl alcohol (100-51-6)

ACGIH : Not applicable

OSHA : Not applicable

#### Water (7732-18-5)

ACGIH : Not applicable

OSHA : Not applicable

#### Cellulose, 2-hydroxyethyl ether (9004-62-0)

ACGIH : Not applicable

OSHA : Not applicable

#### Hydroxyacetic acid (79-14-1)

ACGIH : Not applicable

OSHA : Not applicable

### 8.2. Exposure controls

Hand protection : Wear impervious gloves to minimize skin contact.  
Eye protection : Face shield.  
Skin and body protection : Wear suitable working clothes.  
Respiratory protection : If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Viscous emulsion  
Color : White  
Odor : Mild  
Odor threshold : 10 ppm

# CSP Light Duty Paint Remover

## Safety Data Sheet

pH	: 4.4
Melting point	: < 0 °C
Freezing point	: No data available
Boiling point	: 92.8 °C
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: 15.5 mm Hg @ 20 C
Relative density	: 1
Relative vapor density at 20 °C	: No data available
Solubility	: Water: 57.7 %
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

### 10.3. Possibility of hazardous reactions

Will not occur.

### 10.4. Conditions to avoid

Keep away from heat, sparks and flame. Decomposes when heated above 70-80C

### 10.5. Incompatible materials

Strong mineral acids, oxidizers, or strong alkalis.

### 10.6. Hazardous decomposition products

Oxides of carbon.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Inhalation: Harmful if inhaled.

MasonRE S-305	
ATE US (oral)	500.000 mg/kg body weight
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	11.000 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h
Benzyl alcohol (100-51-6)	
LD50 oral rat	1230 mg/kg
LD50 dermal rabbit	2 g/kg
LC50 inhalation rat (mg/l)	8.8 mg/l/4h
ATE US (oral)	1230.000 mg/kg

# CSP Light Duty Paint Remover

## Safety Data Sheet

<b>Benzyl alcohol (100-51-6)</b>	
ATE US (dermal)	2000.000 mg/kg
<b>Water (7732-18-5)</b>	
LD50 oral rat	> 90 ml/kg
<b>Hydroxyacetic acid (79-14-1)</b>	
LD50 oral rat	1950 mg/kg
LC50 inhalation rat (mg/l)	7100 µg/m <sup>3</sup> (Exposure time: 4 h)
ATE US (oral)	1950.000 mg/kg
Skin corrosion/irritation	: Causes skin irritation. pH: 2.6
Serious eye damage/irritation	: Causes eye irritation. pH: 2.6
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>Benzyl alcohol (100-51-6)</b>	
LC50 fish 1	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
<b>Hydroxyacetic acid (79-14-1)</b>	
LC50 fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

<b>Benzyl alcohol (100-51-6)</b>	
Log Pow	1.1
<b>Hydroxyacetic acid (79-14-1)</b>	
Log Pow	-1.11 (at 19 °C)

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

# CSP Light Duty Paint Remover

## Safety Data Sheet

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Not a dangerous good as defined in transport regulations

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### Benzyl alcohol (100-51-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Water (7732-18-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Cellulose, 2-hydroxyethyl ether (9004-62-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Hydroxyacetic acid (79-14-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. US State regulations

##### Benzyl alcohol (100-51-6)

U.S. - Massachusetts - Right To Know List

U.S. - Minnesota - Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: Other information

Full text of H-phrases::

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
H227	Combustible liquid
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H320	Causes eye irritation
H332	Harmful if inhaled

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*