

CSP Heavy Duty Paint Remover

Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : CSP Heavy Duty Paint Remover

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Paint Stripper

1.3. Details of the supplier of the safety data sheet

Cathedral Stone Products
7266 Park Circle Drive
Hanover, MD 21076
T 410-782-9150

1.4. Emergency telephone number

Emergency number : 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Acute Tox. 4 (Oral) H302
Acute Tox. 4 (Inhalation) H332
Skin Irrit. 2 H315
Eye Irrit. 2B H320

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H302+H332 - Harmful if swallowed or if inhaled
H315 - Causes skin irritation
H320 - Causes eye irritation

Precautionary statements (GHS-US) :

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P264 - Wash thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P312 - If swallowed: Call a poison center/doctor if you feel unwell
P302 + P352 - If on skin: Wash with plenty of water
P304 + P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a poison center/doctor if you feel unwell
P330 - Rinse mouth
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

CSP Heavy Duty Paint Remover

Safety Data Sheet

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Benzyl alcohol	(CAS No) 100-51-6	40 - 45	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312
Water	(CAS No) 7732-18-5	40 - 45	Not classified
Hydroxyacetic acid	(CAS No) 79-14-1	> 10	Acute Tox. 4 (Oral), H302
Cellulose, 2-hydroxyethyl ether	(CAS No) 9004-62-0	0.5 - 2	Not classified

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Obtain medical attention if breathing difficulty persists.
- First-aid measures after skin contact : Rinse with plenty of water. Get medical attention for burns.
- First-aid measures after eye contact : Remove contact lenses immediately. Flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
- First-aid measures after ingestion : Do not induce vomiting. Give water to victim to drink. Seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Harmful if inhaled. May cause respiratory irritation.
- Symptoms/injuries after skin contact : Causes skin irritation. Skin contact produces stinging and a white wound that clears in a short period of time. Prolonged contact may cause more serious burns.
- Symptoms/injuries after eye contact : Causes eye irritation. Eye contact produces stinging and a white wound that clears in a short period of time. Prolonged contact may cause more serious burns.
- Symptoms/injuries after ingestion : Harmful if swallowed. May cause gastrointestinal complications.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use carbon dioxide, foam, dry chemical or water.
- Unsuitable extinguishing media : None.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not flammable.
- Explosion hazard : Vapors can travel to a source of ignition and flash back. Closed containers may explode when overheated. Toxic gases may form when product comes in contact with extreme heat.

5.3. Advice for firefighters

- Protection during firefighting : Firefighters should wear full protective gear.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Stop the flow of material, if this is without risk.

CSP Heavy Duty Paint Remover

Safety Data Sheet

Methods for cleaning up : Confine spill and soak up with absorbent. Place in an approved container and dispose in accordance with local, state and federal regulations.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes and skin. Wash thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect container against physical damage and store in a cool, dry ventilated area. Do not store above 120F (48C).

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Benzyl alcohol (100-51-6)	
ACGIH	Not applicable
OSHA	Not applicable

Water (7732-18-5)	
ACGIH	Not applicable
OSHA	Not applicable

Cellulose, 2-hydroxyethyl ether (9004-62-0)	
ACGIH	Not applicable
OSHA	Not applicable

8.2. Exposure controls

Hand protection : Wear impervious gloves to minimize skin contact.
Eye protection : Face shield.
Skin and body protection : Wear suitable working clothes.
Respiratory protection : If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Viscous.
Color : White
Odor : Mild
Odor threshold : 10 ppm
pH : 2.6
Melting point : < 0 °C
Freezing point : No data available
Boiling point : 99.3 °C
Flash point : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : No data available
Explosion limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Vapor pressure : 15.5 mm Hg @ 20 C
Specific gravity : 1

CSP Heavy Duty Paint Remover

Safety Data Sheet

Relative vapor density at 20 °C	: No data available
Solubility	: Water: 57.7 %
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Will not occur.

10.4. Conditions to avoid

Keep away from heat, sparks and flame. Decomposes when heated above 70-80C

10.5. Incompatible materials

Strong mineral acids, oxidizers, or strong alkalis.

10.6. Hazardous decomposition products

Oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Inhalation: Harmful if inhaled.

MasonRE S-301	
ATE US (oral)	500.000 mg/kg body weight
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	11.000 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h
Benzyl alcohol (100-51-6)	
LD50 oral rat	1230 mg/kg
LD50 dermal rabbit	2 g/kg
LC50 inhalation rat (mg/l)	8.8 mg/l/4h
ATE US (oral)	1230.000 mg/kg
ATE US (dermal)	2000.000 mg/kg
Water (7732-18-5)	
LD50 oral rat	> 90 ml/kg

Skin corrosion/irritation : Causes skin irritation.
pH: 2.6

Serious eye damage/irritation : Causes eye irritation.
pH: 2.6

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

CSP Heavy Duty Paint Remover

Safety Data Sheet

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Benzyl alcohol (100-51-6)	
LC50 fish 1	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Benzyl alcohol (100-51-6)	
Log Pow	1.1

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not a dangerous good as defined in transport regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Benzyl alcohol (100-51-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Cellulose, 2-hydroxyethyl ether (9004-62-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. US State regulations

Benzyl alcohol (100-51-6)	
U.S. - Massachusetts - Right To Know List	
U.S. - Minnesota - Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	

CSP Heavy Duty Paint Remover

Safety Data Sheet

SECTION 16: Other information

Full text of H-phrases::

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
H227	Combustible liquid
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H320	Causes eye irritation
H332	Harmful if inhaled

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product