



WHEN SUBMITTING MASONRY SAMPLES FOR JAHN MORTAR COLOR SELECTION, PLEASE PAY ATTENTION TO THE FOLLOWING:

TAKE SAMPLE(S): Select locations that represent typical color and texture.

Send one sample for each color needed.

Color: **IF THE STRUCTURE WILL BE CLEANED, YOU MUST SEND A CLEANED SAMPLE**
The lab will not clean any samples.

Texture: Send a tooled sample if patch will be tooled.

Sample size: No smaller than 2" x 2" - larger if possible (No Powder!)

MARK SAMPLE(S): **The surface to be matched must be clearly indicated.**

COMPLETE SAMPLE

INFORMATION FORM: Project Manager or Architect must complete the attached form and return it. One form should be completed for each sample being sent. **We cannot begin to process your samples until we receive the form(s) and payment.** Allow 3-10 business days for processing Jahn Color Samples.

SEND SAMPLE(S)
AND FORM TO: Cathedral Stone Products, Inc.
Attn: Color Lab
7266 Park Circle Drive
Hanover, MD 21076
Fax: (410) 782-9155

You Will Receive: One matching dry powder sample

Instructions:

- The dry powder should be mixed and applied on site (from the same location that sample was removed) as a color mock-up.
- Directions for mixing, application, and curing are included or can be found at cathedralstone.com. (The site-applied sample should match our finished laboratory sample)

If your sample matches either a Standard or Premium color, we will email a photo of your sample next to a color puck of our determined color match for your approval.

Please note the following exceptions:

- **Terra Cotta** – We will match your sample to either a Standard/Premium Terra Cotta color or create a custom match to the surface color. To prevent water intrusion, all Terra Cotta repairs must be coated with one of the following Cathedral Stone products: Potassium Silicate Coating/Stain, R97 Water Repellent, or Terra Cotta Glaze.
- **Granite** – It is not possible for us to match the multicolored appearance of granite. We will supply you with a suitable matching background color – the appropriate aggregate (granite dust, etc.) must be added on site to the surface of the damp Jahn mortar; up to 20% of aggregate may be added. It may be necessary, within one or two days, to lightly wash the finished repair with a mild acetic acid (white vinegar) to expose the aggregate.
- **Marble** – The Jahn M120 Marble Repair Mortar will be supplied in a single, solid color. If attempting to simulate “veining”, use Cathedral Stone’s Potassium Silicate Coating/Stain or a darker/lighter Jahn mix applied in “veins” carved into the Jahn repair.

SAMPLE INFORMATION: JAHN MORTAR COLOR MATCH

Please complete this form (one for each sample) and include it when you send us your sample(s). Our lab requires this information to formulate a custom Jahn product. We cannot process your sample without it. **For all sample colors, the lab fee will be required and must be received before the start of the color matching process.** Thank you!

Bill to: _____ Ship To: _____

Phone: _____

Cell: _____

Contact: _____

Email: _____

If you would like to pay the color lab fee by credit card, please complete the following:

Card Number: _____ Security Code: _____ Expiration Date: _____

Card Holder's Name: _____ Card Holder's Signature: _____

Billing Address (if different from above): _____

Building or Project Name: _____

Address: _____

Type of Masonry Requested: _____

(e.g., Brownstone, Limestone, Brick, Terra Cotta, Precast, Pointing Mortar, etc.)

**Pointing Mortar, what type of stone is being repointed? _____

Please answer the following questions about your sample:

Surface to be matched? exposed fractured *(Please mark the sample on the side to be matched)*

Will the building be cleaned? yes no Has the sample been cleaned? yes no

Note: We do not clean samples, if the building has or will be cleaned, the sample to be matched must also be cleaned.

How will the patches be textured? (e.g., smoothed, tooled, left alone) Explain: _____

Do you want your sample(s) returned: yes no

The patches are **(circle one)**: *painted sealed left alone?*

Are you patching steps, pavers or other traffic areas? yes no

How much do you anticipate needing: _____ sq. ft. @ _____ depth (or # of pails: _____) When: _____

Name of Authorized Installer: _____ Authorized Installer #: _____

Submitted by: (Signature) _____

If your sample does not match a Standard or Premium color, do you approve a Custom Jahn Mortar Match (\$238 - color match + 1qt mortar sample)? yes no